

DESCRIPTION

- ADEX EIFS TAPE is a 30 mil SBS modified rubberized asphalt membrane with a polyester top surface.
- The polyester surface enhances the adhesion to trowel-on membranes and base coat materials when applied directly to its surface.
- This air and moisture membrane is an excellent weather resistive barrier.
- The EIFS TAPE is self-sealing when penetrated with mechanical fasteners.

USAGE

- The EIFS TAPE is used to seal window and door openings, over expansion joints, where dissimilar substrates meet and anywhere else water infiltration may be of concern.
- The EIFS TAPE can be applied over gypsum board, wood, metal, styrene and polyethylene surfaces to form a durable air and weather resistant barrier (WRB) membrane in EIFS.

DIMENSIONS

- 4" x 100' (9 rolls / case)
- 6" x 100' (6 rolls / case)
- 9" x 100' (4 rolls / case)
- 12" x 100' (3 rolls / case)

PACKAGING -EIFS TAPE PRIMER

- Available in 3.8 litre container.

COVERAGE - EIFS TAPE PRIMER

- Yields may vary depending upon substrate and surface integrity.
- 23-28m²/3.78L (250-300 ft²/Gal).

COLOUR

- Black (adhering surface)
- White (exposed surface)

THICKNESS

- 30 mils

SUBSTRATE PREPARATION

- Surfaces must be clean, dry, and in good condition, without grease, oil, paint or other bond-inhibiting substances.
- Use of the EIFS TAPE PRIMER is necessary.

INSTALLATION

- Pre-cut the EIFS TAPE into easy-to-handle lengths.
- Peel away the release paper to expose the rubberized asphalt and carefully position the EIFS TAPE against the primed substrate.
- Press the EIFS Tape firmly into place, fully adhering the EIFS TAPE to the substrate.

Water Absorption	
ASTM-D-570	
0.02	
Moisture Vapour Transmission Rate	
ASTM-E-96/B	
1 gm / m ² / 24 hours	
Elongation (Rubber Asphalt Adhesive)	
ASTM-D-2523	
> 170%	

■	Properties
■	Test Method
■	Result

LIMITATIONS

- EIFS TAPE should be applied at a temperature above 7°C (45°F).
- For application below this temperature, the EIFS TAPE must be stored in a heated site.
- Care should be taken not to leave the membrane exposed to direct sunlight for more than 30 days.

STORAGE

- Store materials in a warm area 10°C (50°F) to 32°C (90°F) and protected from moisture and physical damage.
- Keep EIFS TAPE away from direct sunlight and guarded against high heat, flame and sparks.
- The EIFS TAPE must remain in its cardboard box until installation.

This document contains current information on the product. It is only provided as a guide and is subject to modifications at any time without notice. ADEX Systems Inc. reserves the right to make any modification according to technological progress. Specialised designers, architects, engineers or other professionals that choose to make any use of this information bear the complete responsibility, whatever it be, direct or indirect, that could follow from such use. ADEX Systems Inc. does not bear any responsibility that could give way to damages, defaults, defects, deficiencies, prejudices, loss or decrease of profit, be they direct or indirect, resulting from such use of this information by specialised designers, architects, engineers or other professionals. Please refer to www.adex.ca for the latest version of this document.

September 2015